FEATURE HIGHLIGHTS

- 8,500 ANSI LUMENS
- WUXGA RESOLUTION
- 6 OPTIONAL LENSES FOR DIVERSE APPLICATIONS
- HDBASET SUPPORT
- 4K UHD BY HDMI 2.0
- "360° AND PORTRAIT PROJECTION
- FIRMWARE UPGRADE BY LAN













Product Specifications		
Articlenumber		
EAN Code	9H.JMH77.26E 47 8755 08339 6	
Projection System	DLP Single 0.67".WUXGA	
DMD type Native Resolution	DC3 DMD Chip 1920 x 1080 pixels, WUXGA	
Brightness	8,500 ANSI Lumens	
Contrast Ratio	3,000,000 :	
	3.000.000 : 1 1.07 Mrd.	
Display Color	Native 16:10 (6 aspect ratio selectable)	
Aspect Ratio	Laser	
Light Source		
Light Source life*	Normal 20,000/ Eco 38,000/ Dimming 70,000 hours LS2ST1 Wide Zoom: 1.1 ~ 1.3 LS2SD2 Standard: 1.54 ~ 1.93	
Throw Ratio	LS2ST2 Short Throw: 0.77~1.1	LS2LT1 Semi Long: 1.93 ~ 2.9
7 D ::	LS2ST4 Semi Throw: 1.25~1.6	LS2LT2 Long Zoom: 3.0 ~ 5.0
Zoom Ratio	LS2ST1 Wide Zoom: 1.18x	LS2SD2 Standard: 1.25x
	LS2ST2 ShortThrow: 1.42x LS2ST4 SemiThrow: 1.28x	LS2LT1 Semi Long: 1.5x LS2LT2 Long Zoom: 1.67x
Lens Shift	Vertical: -15% ~ 55%, Horizontal: -5%~5%, Standard Lens	
Keystone Correction	Vertical: ± 30 degrees , Horizontal: ± 30 degrees	
Projection Offset	N/A	
Projection Size	50'' ~ 500'', Standard Lens	
Built-in Speaker	10W ×2	
Security	Security Bar, Kensington anti-theft lock slot	
Feature	Rec.709 95%, Blank to True Black, 4K Compatible, DICOM Mode, 360 Degree and Portrait Projection, Corner fit, Custom Lightsource Mode (light power adjustment), Dust Proof Engine, 24/7 Hours Operating, Blanking, Dynamic Dimming, Constant Brightness, Native Resolution Switch Fast mode	
Resolution Support	VGA (640 x 480) to WUXGA (1920	× 1200)
Horizontal Frequency	15 ~102KHz	***
Vertical Scan Rate	23 ~ 120 Hz	
Compatibility	HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	Video Compatibility	NTSC, PAL, SECAM
Power Consumptions	Max 1050W / Normal 950W / Eco 7	
Standby Power consumption	Normal < 0.5 Watts. Network < 2W.	
Power Supply	100 ~ 240V AC	
Product Dimensions (WxHxD)	$525 \times 216 \times 470$ mm (with feets)	
Product Weight	24 kg (without Lens)	
Noise Level	Normal 43 dBA / Eco 36 dBA	
Operating Temperature	0 ~ 40 degrees	
Accessories	Standard	Optional
	Installation Guide	Instashow WDC10/WDC20
	Safety Guide	Ceiling Mount (CMG6)
	Remote Control	LS2ST1 Wide Zoom (51,IDH37.011)
	AA Battery ×2	LS2ST2 Short Throw (5A.JK337.001)
	VGA cable (1,8m)	LS2ST4 SemiThrow (5.A.JK337.011)
	Power Cord	LS2SD2 Standard (5],[EN37.001)
	Warranty card (by Region)	LS2LT1 Semi Long (5J.JDH37.032)
	3pin VESA to BNC Kabel	LS2LT2 Long Zoom (5I,IDH37.041)
On Screen Display Language		/ Danish / Dutch / English / Finnish / French / German / Greek / Hindi / Hungarian / Italian / Indonesian /
		sh / Portuguese / Rumanian / Russian / Simplified Chinese / Spanish / Swedish / Turkish / Thai / Traditional

^{*}LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

5 years

Guarantee

^{*}The Contrast is measure by Full On Full Off standard.





^{*}All related Optical Value is measure by Standard Lens.

Input and Output Terminals

Dimensions



- LAN (RJ45)
- Monitor out (D-sub 15pin) 2
- USB (Type A) 3
- PC (D-sub 15pin) 4
- 6 HDBaseT
- DVI-D
- Composite Video in (RCA)
- HDMI I (HDCP 2.2)
- HDMI 2 (HDCP 2.2)

- **(** RS232 (DB-9pin) in / out
- PC2 (5BNC,YPbPr)
- 3D Sync in / out
- Audio L/R in / out (RCA)
- Service
- (Audio in (Mini Jack)
- (6) Wired Remote in / out
- DC 12V Trigger (3.5mm Jack)



Ceiling Mount Chart



