



WIRE ADDRESS

P1	P2	P1	P2
1	1	14	14
2	2	15	15
3	3	16	16
4	4	17	17
5	5	18	18
6	6	19	19
7	7	20	20
8	8	21	21
9	9	22	22
10	10	23	23
11	11	24	24
12	12	25	25
13	13	Shell	Shell

- Electrical Test:
1. 100% TEST OPEN SHORT MIS-WIRE.
 2. CONTACT RESISTANCE: 3Ω MAX.
 3. INSULATION RESISTANCE: 5MΩ MIN.
 4. HI-POT: 300V DC/10MS.

NUMBER	1	2	4	Quantity	Unit
F	45P PVC BEIGE			G	
D	Screw: #4-40UNC(Nickel Plated, Beige)			4	PCS
C	DB 25P FEMALE(Blue Insulator, Nickel Plated)			1	PCS
B	DB 25P MALE(Blue Insulator, Nickel Plated)			1	PCS
A	NON-UL 30AWG*25C + AD. OD=7.0mm BEIGE PVC JACKET.			1	PCS

ROLINE RS-232 Cable, DB25 M - F, 1.8m	
Item	11.01.3618
Draw	<i>Shake</i> Date: 2020.05.13
Approval	
Duty	F16 BOM.NO.:13891

