



Electrical Test:

1. Real Test Passed 1920 x 1080 @60Hz
2. Real Test, Not Twinkling, Double Vision and Decolor

ITEM NO.	L(mm)	T(mm)
11.04.5970	1000	+30/-0mm
11.04.5971	1500	+30/-0mm
11.04.5972	2000	+30/-0mm
11.04.5973	3000	+50/-0mm
11.04.5974	5000	+50/-0mm

NUMBER	PRODUCT SPECIFICATION	Q'TY	UNIT
G	45P PVC BLACK		G
F	SCREW: Ø4-40 UNC; Ø2.3*32mm	2	PCS
E	DP MALE SHELL (BLACK ABS)	1	PCS
D	PCB'A (IC:RTD2166)	1	PCS
C	HDB 15P MALE (BLACK INSULATOR, GOLD PLATED)	1	PCS
B	DP MALE (BLACK INSULATOR, GOLD PLATED)	1	PCS
A	UL20276 (32#*1P+D+AL/MY)*5+32#*5C+ADB, OD: 5.5mm, BLACK PVC JACKET	1	PCS

ROLINE DisplayPort to VGA Cable, DP-VGA, M/M, black			
Item	11.04,5970, 11.04.5971, 11.04.5972, 11.04.5973, 11.04.5974		
Draw	<i>Kobe</i>	Date:	2019.08.27
Approval			
Duty			BOM.NO:
Sample NO.			Drawings of 1 (2) Proportion: 1:1 Unit(mm)

