



NOTE:

1. Electrical properties:

- 1.1 Tested by (quantum data)780E handheld test Instrument for DP1.2 21.6G 480P , 720P , 1080P, 4K*2K/60HZ PASS DDC, (EDID), Hot plug. PASS
- 1.2 100% PC test pass DP1.2 3840*2160 60HZ RGB/YUV444

2. RoHS compliant.

PRINTING:HIGH SPEED CABLE E324703 AWM STYLE 20276 80 C 30V

MATERIAL LIST

⑥	DUST COVER	PE, COLOR: TRANSPARENT	2
⑤	OUTER MOLD	ABS SHELL, COLOR:BLACK	1
④	CABLE	(7/0.10BC*1P+7/0.10BC+ AM)* 5PCS+7/0.12BC*5C+AM+7/0.12BC+128/0.12 AL-MG+PVC, OD: 7.3±0.1mm, COLOR: BLACK	L
③	OUTER MOLD	ABS SHELL, COLOR: BLACK	2
②	OUTER MOLD	BLACK PVC	2
①	CONNECTOR	DP MALE,GOLD PLATED PIN,NICKEL PLATED SHELL	2
No.	PART NAME	DESCRIPTION	QTY

NAME	VALUE Active DisplayPort Cable, v1.2, M/M, 15m, black
Item No.	14.99.3495



MAPE	TOLERANCE	
	X.	±1.00
	X.X	±0.50
DRAW BY	SCALE	MM
	PAGE	1/1