



Comply with LSOH standard DIN EN50525-3-11	
Polarity and Conduction and Penetration Test	
Dielectric Voltage Withstand Test : 2000V / 1 Sec	
Electrical Performance (20°C)	
Item	Parameter
Conductor Resistance	≤19.5Ω/1000m
Voltage Rating	AC 300/500V

Customer Item NO.	Cable Color	Molding Color	Length (MM)
19.44.1012	Black	Black	3000±30
19.44.1017	White	White	3000±30

⑨	Mini TIE	Brown paper tie	2PCS
⑧	Current Label	Stickers provided by customers	1PC
⑦	Current Label	Recycle logo stickers	1PC
⑥	Molding	Molding 40P LSOH(TPE)	AR
⑤	Housing	SF-82F Three plug piece of inner frame,IEC-C13,PC	1SET
④	Housing	SF-81F Three plug piece of inner frame,IEC-C14, PC	1SET
③	Terminal	SF-82F IEC C13 Three plug Female Straight insert Common of terminal,Brass yellow,1.0mm <sup>2</sup>	3PCS
②	Terminal	SF-81F IEC C14 Three plug male straight insert common of terminal,Nickel plated,1.0mm <sup>2</sup>	3PCS
①	CABLE	H05Z1Z1-F 3G 1.0MM <sup>2</sup> LSOH(polyolefin resin)	1PC
No.	TITLE	DESCRIPTION	Q'TY

⑧ Stickers provided by customers

⑨ Wrap the tie 2 times

170±20

SECOMP

PINOUT			
SF-81F		SF-82F	WIRE
E		E	YE/GN
L		L	BROWN
N		N	BLUE

DRAW. NO	GFAC-S220224	TITLE	ROLINE GREEN Extension Power Cable, IEC320 C14/C13, LSOH		
CUSTOMER	--	DRAW	LQF	DATE	2023.09.05
CUST' R P/N	--	CHECK	宋正博 2023.09.05	DATE	--
SCALE	1:1	APPROVED		SHEET	1 of 1

Unless specified on the drawing, tolerances are per the follows:

X.	±0.20	X°	±3
.X	±0.10	.X°	±0.3
.XX	±0.05		