

# KEENETIC



## HERO **DSL**

**AC1300 Mesh Wi-Fi 5 Supervectoring VDSL2/ADSL2+ Modem Router with a 5-Port Gigabit Smart Switch, USB 2.0 and USB 3.0 Ports**

### KEY FEATURES

- **Model number**  
KN-2410
- **CPU**  
EN7516GT 900 MHz, dual core
- **RAM**  
256 MB DDR3
- **Flash memory, Dual Image**  
128 MB
- **Wi-Fi 2.4 + 5 GHz**
- **Wi-Fi class**  
AC1300
- **Antennas**  
5 dBi
- **Ethernet ports**  
5 x 1 Gbps
- **WPS/Wi-Fi button**
- **FN button**  
Yes, two buttons
- **USB ports**  
1 x USB 2.0, 1 x USB 3.0
- **3G/4G connection**  
Via a compatible USB modem
- **DSL connection**  
Built-in ADSL2+/VDSL2 modem
- **Telephony support**  
With Keenetic Linear (sold separately)
- **Mesh Wi-Fi System**

### PERFORMANCE

- **2,4 GHz Wi-Fi network**  
400 Mbit/s\*
- **5 GHz Wi-Fi network**  
867 Mbit/s\*
- **IPoE/PPPoE routing**  
Up to 1800 Mbit/s in duplex
- **L2TP/PPTP routing**  
Up to 800 Mbit/s
- **Reading from a USB drive**  
Up to 90 MB/s (USB 3.0)

### DSL PROTOCOL SUPPORT

- **Automatic selection of ADSL modulation**
- **G.Dmt, G.Lite, ADSL2, ADSL2+**
- **The maximum number of PVC**  
8
- **VDSL2, 8a, 8b, 8c, 8d, 12a, 12b, 17a, 30a profiles**
- **VDSL2, 35b profile**
- **G. vector support**

## WIRELESS NETWORK

- Seamless roaming 802.11k/r/v
- MU-MIMO
- Airtime Fairness
- Beamforming
- Pre-configured Wi-Fi protection
- WEP, WPA-PSK
- WPA2-PSK, WPA2-Enterprise
- WPA3-PSK, WPA3-Enterprise, OWE
- Multi-SSID and Guest Network
- Access control by MAC address
- Wi-Fi Multimedia (WMM)

## FEATURES AND PROTOCOLS

- IPoE, PPPoE, PPTP, L2TP, 802.1x
- Multi-WAN
- Policy routing
- Internet connection backup
- Ping Check connectivity monitor
- PPPoE/PPTP/L2TP pass-through
- VLAN IEEE 802.1Q
- Routing table (DHCP/Manual)
- IntelliQoS
- DHCP (client/server)
- IPv6 Dual Stack
- NAT
- IGMP
- UDP to HTTP proxy
- UPnP
- Manual port forwarding
- SPI firewall with protection against DoS attacks
- PPTP (client/server)
- L2TP over IPsec client/server
- OpenVPN client/server
- SSTP client/server
- Ethernet-over-IP, IP-IP, GRE
- IPsec VPN (client/server)
- WireGuard
- Dynamic DNS client
- Direct or cloud access via KeenDNS
- HTTPS security for access via KeenDNS
- Cloudflare DNS
- AdGuard ad blocker
- Traffic statistics per client
- Bandwidth limit per client
- Access schedule per client or interface
- Guest hotspot with authentication (Captive Portal)

## USB APPLICATIONS

- 3G and 4G (LTE) USB modems support
- RAS, NDIS, CDC-Ethernet, QMI support
- File server and personal cloud
- FAT, FAT32, exFAT, NTFS, EXT2, EXT3, EXT4, HFS+ support
- CIFS/SMB
- AFP
- FTP, SFTP
- WebDAV
- Time Machine, File History support
- Support for third-party extension packages from the Entware and Debian repositories
- Download Station
- File server
- Media server
- Print server

## TROUBLESHOOTING AND MANAGEMENT


- Mobile app for Android and iOS
- Web Interface with the Initial Setup Wizard and HTTPS security
- Command Line (CLI) via TELNET/SSH
- An option to control from external network
- Backup and restore configuration
- Automatic OS updates
- System event logging

## PHYSICAL SPECIFICATIONS AND ENVIRONMENT REQUIREMENTS



- **Device dimensions excluding antenna, w x d x h**  
214 mm x 154 mm x 33 mm
- **Device weight**  
536 g
- **Operating temperature**  
0–40°C
- **Operating humidity**  
20%–95% non-condensing
- **Power supply voltage**  
100–240 V 50/60 Hz

## PACKAGE CONTENTS

- Device
- Power adapter
- Ethernet cable
- Telephone cable
- DSL splitter
- Quick start guide



1. Status LED
2. Internet LED
3. FN1 & FN2 LEDs
4. Wi-Fi LED
5. Wi-Fi Control Button
6. Wi-Fi Antennas
7. Reset Button
8. Network Ports 1, 2, 3 & 4
9. Network Port 0
10. DSL Port
11. DC Power Socket
12. FN1 & FN2 Buttons
13. USB 3.0 & USB 2.0 Port



## Ordering information

Model name	Part-number	Short description
Keenetic Hero DSL (KN-2410)	KN-2410-01-EN	AC1300 Mesh Wi-Fi 5 Supervectoring VDSL2/ADSL2+ Modem Router with a 5-Port Gigabit Smart Switch, USB 2.0 and USB 3.0 Ports

\*400 and 867 Mbps are maximum wireless signal rates derived from 802.11n(256QAM)/ac specifications, used when connecting to clients using two spatial streams and an 40/80 MHz channel bandwidth for transmission and reception. Actual data throughput and wireless coverage will vary and may be lowered by the features and settings of the equipment, the number of client devices in the network, obstacles to signal propagation, the presence of other wireless networks, and/or radio interference.

## KEENETIC

© Keenetic Ltd., 2022. All rights reserved.

Names of products or companies mentioned herein may be the trademarks or service marks of their respective owners. Keenetic Ltd. reserves the right to make changes and improvements to any product without prior notification.