



MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION
①	CABLE	UTP [24AWG 7*0.19±0.015mm((Bare Copper)*1PR)*4+PVC OD:5.8±0.3mm COLOR:GREY
②	RJ45 CONNECTOR	RJ45,8P8C,TWO FORK GOLD PLATED CONTACTS
③	MOLDING	MOLDING PVC , COLOR:GREY

(1)Jacket Color:Grey(RAL 7044)  
(2)wiring:T568B

Item No.	Length (M)	Tolerance (MM)
21.99.0870	0.5	+20/-10
21.99.0871	1	+/-20
21.99.0872	2	+/-40
21.99.0873	3	+/-60
21.99.0875	5	+/-110
21.99.0876	7	+/-140
21.99.0877	10	+/-200
21.99.0878	15	+/-310
21.99.0879	20	+/-400

Marking: E213738 CM (UL) C(UL) UTP PATCH CORD 24AWG 4P ISO/IEC 11801 AND TIA/EIA 568 CAT6A

ELECTRONIC TEST:

- A. OPEN/SHORT : 100%
- B. WORKING TEMPERATURES:-20~60°C
- C. Minimum Banding Radius: 46MM

Item No.	21.99.0870	21.99.0871	21.99.0872	21.99.0873	21.99.0875
	21.99.0876	21.99.0877	21.99.0878	21.99.0879	
REMARK: NO	CHA NO	DESC	VALUE UTP Cat. 6a Patch Cord, grey		
DRAWN BY	WEIHAIYAN		<b>SECOMP</b>		
APPROVED BY	MORGAN				
DATE	2015.09.22				